



# PRODUCT DATA SHEET

## ANTI-DROSS #7

January, 2008

### DESCRIPTION

- ◆ **Anti-dross # 7** melts at soldering temperatures into an oily substance and will remove the "good" solder from the solder dross. The anti-dross # 7 can also be used as a blanket on the surface of the solder pot to prevent dross formation. When used at regular intervals the Anti-Dross # 7 can totally eliminate your solder dross problems. When spread overnight inside the solder-nozzle (chimney), the Anti-Dross #7 will thoroughly clean baffles and eliminate removal and maintenance. Daily additions will keep your **solder wave dynamics consistent**.
- ◆ **Anti-dross # 7** has a **clean, non-irritating odor**, but it must be vented properly to insure good working conditions. After use, the material can be disposed of in any approved waste container.

### PHYSICAL PROPERTIES

<b>Appearance</b>	Off White flake
<b>Melting Point</b>	55 °C / 130 °F
<b>Boiling Point</b>	> 315 °C / 600°F

**SAFETY** **Anti-dross # 7** is a non-hazardous material. Material Safety Data Sheets are available upon request.

**PACKAGING** **Anti-dross # 7** is available in 4Lb and 20Lb pails.

**STORAGE** **Anti-dross # 7** has an indefinite shelf life when stored in the original sealed container at ambient temperatures.

**“Our commitment to quality and customer service is our most valuable asset”**

The information contained herein is offered free of charge for use by technically qualified personnel at their discretion and risk. All information and recommendations contained herein are based on test and data which we believe to be reliable, but the accuracy or completeness is not guaranteed and no warranty of any kind is made with respect hereto.

Interflux USA, Inc.  
2914 Ladybird Lane  
Dallas, TX 75220

Tel: 214-350-5565  
Toll Free: 800-843-3589  
Fax: 214-350-9713

[www.interfluxusa.com](http://www.interfluxusa.com)